DINGO®

WARRANTY
5 YRS / 5,000 HRS



K9CT

WWW.DINGO.COM.AU

WHAT YOU GET

- The ORIGINAL DiNGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish

PERFORMANCE

Engine	27 HP Yanmar
Hydraulic pumps	3 pumps
Pump sizes	6, 8.4 & 8.4 cc
Relief pressure (AUX)	3,400 psi (235 bar)
Hydraulic output	73 L/m
Max travel speed	9.5 km / h
Rated lift capacity	440 kg

1 **Direct drive trax system**
Through 2 specifically designed and OEM manufactured Hydraulic Drive Motors

2 **High Flow Auxiliary Hydraulics**
For powering attachments through the toughest conditions.

3 **Grease free**
For Lower Cost maintenance and Quick hitch system.

4 **180° access**
Safer for operators - no risk of being trapped from behind and side bars.

5 **Soft touch controls**
Minimise fatigue while providing accurate control.

6 **1,855mm lift**
Lifts into utes & most trucks, tips over fences.

7 **Rupture resistant fuel tank**
Full vented cap with true-fill opening for easier refuelling.

E&OE (Errors and omissions excepted).

DIMENSIONS

Overall width	1,020 mm
Overall length	1,600 mm
Overall height	1,225 mm
Max operating height 4 in 1	2,680 mm
Turning radius with 4 in 1 bucket	1,300 mm
Angle of departure	25°
Wheel base	800 mm
Ground clearance	155 mm
Dump height standard bucket	1,550 mm
Dump height 4 in 1 bucket	1,870 mm
Reach fully raised 4 in 1 bucket	800 mm
Height to hinge pin	1,985 mm
Machine width 4 in 1 bucket	1,050 mm & 1,200 mm
Hydraulic reservoir capacity	76 L
Machine mass	1,180 kg
Warranty	5 yrs / 5,000 hrs

(In accordance with Dingo warranty Terms & Conditions)



WWW.DINGO.COM.AU

DINGO®