DINGO®

WARRANTY
5 YRS / 5,000 HRS



K9DT

WWW.DINGO.COM.AU

WHAT YOU GET

- The ORIGINAL DiNGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish

PERFORMANCE

Engine	27 HP Yanmar Diesel
Hydraulic pumps	2 pumps
Pump sizes	11 & 4 cc
Relief pressure (AUX)	3,200 psi (220 bar)
Hydraulic output	47 L/m
Max travel speed	7.5 km / h
Rated lift capacity	325 kg

DIMENSIONS

Overall width	1,020 mm
Overall length	1,600 mm
Overall height	1,200 mm
Max operating height 4 in 1	2,680 mm
Turning radius with 4 in 1 bucket	1,300 mm
Angle of departure	25°
Wheel base	800 mm
Ground clearance	155 mm
Dump height standard bucket	1,450 mm
Dump height 4 in 1 bucket	1,835 mm
Reach fully raised 4 in 1 bucket	800 mm
Height to hinge pin	1,940 mm
Machine width 4 in 1 bucket	1,050 mm & 1,200 mm
Hydraulic reservoir capacity	76 L
Machine mass	1,093 kg
Warranty	5 yrs / 5,000 hrs

(In accordance with Dingo warranty Terms & Conditions)

1 Direct drive trax system
Through 2 specifically designed and OEM manufactured Hydraulic Drive Motors

2 High Flow Auxiliary Hydraulics
For powering attachments through the toughest conditions.

3 Grease free
For Lower Cost maintenance and Quick hitch system.

4 180° access
Safer for operators - no risk of being trapped from behind and side bars.

5 Soft touch controls
Minimise fatigue while providing accurate control.

6 1,855mm lift
Lifts into utes & most trucks, tips over fences.

7 Rupture resistant fuel tank
Full vented cap with true-fill opening for easier refuelling.



E&OE (Errors and omissions excepted).

WWW.DINGO.COM.AU

DINGO®