

# DINGO®

**WARRANTY**

5 YRS / 5,000 HRS



**K9PW**

[WWW.DINGO.COM.AU](http://WWW.DINGO.COM.AU)

# WHAT YOU GET

- The ORIGINAL DiNGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish
- Narrow wheel option for tight spaces

# PERFORMANCE

Engine	23 HP Kohler Petrol
Hydraulic pumps	2 pumps
Pump sizes	11 & 4 cc
Relief pressure (AUX)	3,200 psi (220 bar)
Hydraulic output	47 L/m
Max travel speed	7.5 km / h
Rated lift capacity	325 kg

## All wheel drive system

- 1 Through 4 specifically designed and OEM manufactured Hydraulic Drive Motor

## High Flow Auxiliary Hydraulics

- 2 For powering attachments through the toughest conditions.

## Grease free

- 3 For Lower Cost maintenance and Quick hitch system.

## 180° access

- 4 Safer for operators - no risk of being trapped from behind and side bars.

## Soft touch controls

- 5 Minimise fatigue while providing accurate control.

## 1,840mm lift

- 6 Lifts into utes & most trucks, tips over fences.

## Rupture resistant fuel tank

- 7 Full vented cap with true-fill opening for easier refuelling.

# DIMENSIONS

Overall width	780 mm & 1,040 mm
Overall length	1,600 mm
Overall height	1,200 mm
Max operating height 4 in 1	2,680 mm
Turning radius with 4 in 1 bucket	1,300 mm
Angle of departure	25°
Wheel base	800 mm
Ground clearance	140 mm
Dump height standard bucket	1,450 mm
Dump height 4 in 1 bucket	1,835 mm
Reach fully raised 4 in 1 bucket	800 mm
Height to hinge pin	1,940 mm
Machine width 4 in 1 bucket	1,050 mm & 1,200 mm
Hydraulic reservoir capacity	76 L
Machine mass	862 kg
Warranty	5 yrs / 5,000 hrs

*(In accordance with Dingo warranty Terms & Conditions)*



E&OE (Errors and omissions excepted).